

TECHNICAL CHARACTERISTICS DRY DOUBLE AND TRIPLE TABLE





DIMENSIONS

DOUBLES: Heights 74,5/ 100: 300x80/ 300x100/ 300x120/ 360x80/ 360x100/ 360x120/ 400x80/ 400x100/ 400x120/ 440x80/ 440x100/ 440x120

TRIPLES: Heights 74,5/ 100: 540x80/ 540x100/ 540x120/ 600x80/ 600x100/ 600x120/ 660x80/ 660x100/ 660x120

Free height 69,5 cm for 74,5 height, 95 cm for 100 height.

WEIGHT

44/45 (300x80)	81/82 (400x100)	160/161 (540x120)
61/62 (300x100)	96/97 (400x120)	130/131 (600x80)
78/79 (300x120)	72/73 (440x80)	149/150 (600x100)
51/52 (360x80)	89/90 (440x100)	168/169 (600x120)
73/74 (360x100)	106/107 (440x120)	138/139 (660x80)
95/96 (360x120)	124/125 (540x80)	172/173 (660x100)
66/67 (400x80)	142/143 (540x100)	206/207 (660x120)

PACKAGING

1 bulto por caja

ACCESSORIES

Access hole
Cable guide tray
CPU holder

Top access (white or black)
Leg cable tray
Drawers

Top access + standard
power/ data (white or black)
Protector screen

ORIGIN

100% made in Europe

DESIGN

Ondarreta team

1. COMPONENTS

1.1. LEGS

MATERIAL

30 mm (1.2") side and 2 mm (0.08") thickness cold laminated St-37 quality steel tube.
Tensile Strength: 340-470 N/mm² (49,300-68,160 psi);
Elastic Limit > 235 N/mm² (32,080 psi); Elongation > 25%,
Surface Hardness > 110 HB.

FINISH

Colour epoxy

1.2. TABLETOP

LAMINATE

High pressure laminate glued and pressed in high temperatures on a 20 mm (0.8") thickness technical wood table. It's edged with a PVC panel glued with a special hot melt adhesive.

LAMINATE + BIRCH PLYWOOD

High pressure laminate glued and pressed in high temperatures on a 20mm (0.8") thickness birch wood table.

FENIX + BIRCH PLYWOOD

Fenix sheet glued and pressed in high temperatures on a 20 mm (0.8") thickness birch wood table.

Fenix is an extremely opaque, anti-fingerprint and nanotechnological material that heals superficial micro-scratches.

BEECH

Beech plywood board shell, 20 mm (7.9") thick CNC machined.

OAK

20 mm natural Oak wood panel glued and pressed in high temperatures on a technical wood table. It's edged with a natural Oak wood panel glued with a special hot melt adhesive.

Tabletop's technical characteristics:

Urea-formol glue: low formaldehyde emission (E1 European Normative)
The wood has the PEFC certificate.

FINISH:

Stained, laminate or fenix.

2. METAL FINISHES

2.1. EPOXYS

Powder covering formulated with polyester resins, with good both mechanical and chemical properties, outdoor maximum resistance and noxious compounds free. Electrostatic application and oven cured at 200°C (392°F).

Technical Characteristics:

Thickness (ISO 2360): between 60 and 90 µm.
Adherence (ISO 2409): Grade: 0 (maximum adherence)

3. WOOD FINISHES

3.1. STAIN

Pigmented enamel with a transparent stain coating. Reactive drying paints: excellent adherence between layers and better mechanical resistance.

Technical Characteristics:

Satisfying UNE-EN 71-3 normative; Formaldehyde free compounds.

4. PHOTOS



